

Sonicrafter®

SAFETY AND OPERATING MANUAL
ORIGINAL INSTRUCTIONS

Oscillating Multi-Tool WX686 WX686.X

PRODUCT SAFETY

GENERAL POWER TOOL

SAFETY WARNINGS



WARNING: Read all safety

warnings, instructions, illustrations and specifications provided with this power tool.

Failure to follow all instructions listed below may result in electric shock, fire and/or serious injury.

Save all warnings and instructions for future reference.

The term "power tool" in the warnings refers to your mains-operated (corded) power tool or battery-operated (cordless) power tool.

1) Work area safety

- a) **Keep work area clean and well lit.** Cluttered or dark areas invite accidents.
- b) **Do not operate power tools in explosive atmospheres, such as in the presence of flammable liquids, gases or dust.** Power tools create sparks which may ignite the dust or fumes.
- c) **Keep children and bystanders away while operating a power tool.** Distractions can cause you to lose control.

2) Electrical safety

- a) **Power tool plugs must match the outlet.** Never modify the plug in any way. Do not use any adapter plugs with earthed (grounded) power tools. Unmodified plugs and matching outlets will reduce risk of electric shock.
- b) **Avoid body contact with earthed or grounded surfaces, such as pipes, radiators, ranges and refrigerators.** There is an increased risk of electric shock if your body is earthed or grounded.
- c) **Do not expose power tools to rain or wet conditions.** Water entering a power tool will increase the risk of electric shock.
- d) **Do not abuse the cord.** Never use the cord for carrying, pulling or unplugging the power tool. Keep cord away from heat, oil, sharp edges or moving parts. Damaged or entangled cords increase the risk of electric shock.
- e) **When operating a power tool outdoors, use an extension cord suitable for outdoor use.** Use of a cord suitable for outdoor use reduces the risk of electric shock.
- f) **If operating a power tool in a damp location is unavoidable, use a residual current device (RCD) protected supply.** Use of an RCD reduces the risk of electric shock.

3) Personal safety

- a) **Stay alert, watch what you are doing and use common sense when operating a power tool.** Do not use a power tool while you are tired or under the influence of drugs, alcohol or medication. A moment of

inattention while operating power tools may result in serious personal injury.

- b) **Use personal protective equipment. Always wear eye protection.** Protective equipment such as dust mask, non-skid safety shoes, hard hat, or hearing protection used for appropriate conditions will reduce personal injuries.
 - c) **Prevent unintentional starting. Ensure the switch is in the off-position before connecting to power source and/or battery pack, picking up or carrying the tool.** Carrying power tools with your finger on the switch or energising power tools that have the switch on invites accidents.
 - d) **Remove any adjusting key or wrench before turning the power tool on.** A wrench or a key left attached to a rotating part of the power tool may result in personal injury.
 - e) **Do not overreach. Keep proper footing and balance at all times.** This enables better control of the power tool in unexpected situations.
 - f) **Dress properly. Do not wear loose clothing or jewellery. Keep your hair and clothing away from moving parts.** Loose clothes, jewellery or long hair can be caught in moving parts.
 - g) **If devices are provided for the connection of dust extraction and collection facilities, ensure these are connected and properly used.** Use of dust collection can reduce dust-related hazards.
 - h) **Do not let familiarity gained from frequent use of tools allow you to become complacent and ignore tool safety principles.** A careless action can cause severe injury within a fraction of a second.
- #### **4) Power tool use and care**
- a) **Do not force the power tool. Use the correct power tool for your application.** The correct power tool will do the job better and safer at the rate for which it was designed.
 - b) **Do not use the power tool if the switch does not turn it on and off.** Any power tool that cannot be controlled with the switch is dangerous and must be repaired.
 - c) **Disconnect the plug from the power source and/or remove the battery pack, if detachable, from the power tool before making any adjustments, changing accessories, or storing power tools.** Such preventive safety measures reduce the risk of starting the power tool accidentally.
 - d) **Store idle power tools out of the reach of children and do not allow persons unfamiliar with the power tool or these instructions to operate the power tool.** Power tools are dangerous in the hands of untrained users.
 - e) **Maintain power tools and accessories.** Check for misalignment or binding of moving parts, breakage of parts and any other condition that may affect the power tool's operation. If damaged, have the

power tool repaired before use. Many accidents are caused by poorly maintained power tools.

- f) Keep cutting tools sharp and clean.** Properly maintained cutting tools with sharp cutting edges are less likely to bind and are easier to control.
- g) Use the power tool, accessories and tool bits etc. in accordance with these instructions, taking into account the working conditions and the work to be performed.** Use of the power tool for operations different from those intended could result in a hazardous situation.
- h) Keep handles and grasping surfaces dry, clean and free from oil and grease.** Slippery handles and grasping surfaces do not allow for safe handling and control of the tool in unexpected situations.

5) Service













- a) Have your power tool serviced by a qualified repair person using only identical replacement parts.** This will ensure that the safety of the power tool is maintained.


SAFETY INSTRUCTION FOR CUTTING







Hold power tool by insulated gripping surfaces, when performing an operation where the cutting accessory may contact hidden wiring or its own cord. Cutting accessory contacting a "live" wire may make exposed metal parts of the power tool "live" and could give the operator an electric shock.




SYMBOLS

| | |
|--|---|
|  | To reduce the risk of injury, user must read instruction manual |
|  | Warning |
|  | Wear ear protection |
|  | Wear eye protection |

| | |
|---|--|
|  | Wear dust mask |
|  | Double insulation |
|  | Make sure the tool is unplugged prior to changing accessories. |
|  | Before working with your tool make sure that no power cords will be damaged. |
|  | Avoid danger of injury from the sharp edges of the accessories. |
|  | Accessories can become very hot while working, presenting danger of burns! |
|  | Wear protective gloves |
|  | High oscillation frequency. |
|  | Low oscillation frequency. |
|  | Lock |
|  | Unlock |
|  | Waste electrical products must not be disposed of with household waste. Please recycle where facilities exist. Check with your local authorities or retailer for recycling advice. |







COMPONENT LIST

| |
|-------------------------------|
| 1. ONBOARD CLIP-IN WRENCH |
| 2. ON/OFF SWITCH |
| 3. VARIABLE SPEED CONTROL |
| 4. VENTING SLOTS |
| 5. UNIVERSAL FIT™ INTERFACE * |
| 6. FLANGE |

*Works with other oscillating tool brands' accessories.
The following compatible brands are trademarks owned by third parties which may be registered by their respective owners: Black & Decker®, Bosch®, Chicago Electric®, Craftsman®, Dremel®, Fein®, Genesis®, Makita®, Mastercraft®, Milwaukee®, Performax®, Porter Cable®, Ridgid®, Ryobi®, Skil®, Rockwell, ShopSeries® and Tool Shop®.
Not all the accessories illustrated or described are included in standard delivery.

TECHNICAL DATA

Type **Designation WX686 WX686.X**
(6-designation of machinery, representative of Oscillating Multi-Tool)

| Model | WX686 WX686.X** |
|-------------------|-----------------|
| Rated voltage | 230-240V~50Hz |
| Rated power input | 250W |
| No load speed | 11000-20000/min |
| Oscillation angle | 3.2° |
| Protection class | □/II |
| Tool weight | 1.45kg |

**X=1-999,A-Z,M1-M9 there are only used for different customers, there are no safe relevant changes between these models.

We recommend that you purchase your accessories from the same store that sold you the tool. Refer to the accessory packaging for further details. Store personnel can assist you and offer advice.

NOISE INFORMATION


| | |
|-----------------------------------|-----------------------------|
| A weighted sound pressure | L _{PA} : 77.7dB(A) |
| A weighted sound power | L _{WA} : 88.7dB(A) |
| K _{PA} & K _{WA} | 3 dB(A) |
| Wear ear protection | |

VIBRATION INFORMATION


Vibration total values (tri-ax vector sum) determined according to EN 62841:

| |
|--|
| Vibration emission value: |
| a _n = 4.766m/s ² Uncertainty K = 1.5m/s ² |

The declared vibration total value and the declared noise emission value have been measured in accordance with a standard test method and may be used for comparing one tool with another. The declared vibration total value and the declared noise emission value may also be used in a preliminary assessment of exposure.

**WARNING:** The vibration and noise emissions during actual use of the power tool can differ from the declared value depending on the ways in which the tool is used especially what kind of workpiece is processed dependant on the following examples and other variations on how the tool is used:
How the tool is used and the materials being cut or drilled.
The tool being in good condition and well maintained.
The use of the correct accessory for the tool and ensuring it is sharp and in good condition.
The tightness of the grip on the handles and if any anti vibration and noise accessories are used.
And the tool is being used as intended by its design and these instructions.

This tool may cause hand-arm vibration syndrome if its use is not adequately managed.

**WARNING:** To be accurate, an estimation of exposure level in the actual conditions of use should also take account of all parts of the operating cycle such as the times when the tool is switched off and when it is running idle but not actually doing the job. This may significantly reduce the exposure level over the total working period.
Helping to minimise your vibration and noise exposure risk.
Always use sharp chisels, drills and blades.
Maintain this tool in accordance with these instructions and keep well lubricated (where appropriate).

If the tool is to be used regularly then invest in anti vibration and noise accessories.
Plan your work schedule to spread any high vibration tool use across a number of days.

OPERATING INSTRUCTIONS



NOTE: Before using the tool, read the instruction book carefully.

INTENDED USE

The power tool is intended for sawing and remodeling wooden materials, plastic, plaster, non-ferrous metals and fasteners (e.g. nails and clamps) as well as for working on soft wall tiles and for dry grinding of small surfaces. It is especially suitable for working close to edges and for flush cutting.

ASSEMBLY AND OPERATION

| Action | Figure |
|--|---------------------|
| Mounting accessories | |
| --Remove the onboard Clip-in wrench | See Fig. A |
| --Loosen the flange and insert accessories | See Fig. B1, B2, B3 |
| --Tighten the flange | See Fig. C |
| --Store the onboard Clip-in wrench | See Fig. D, E |
| Operating the on/off switch | See Fig. F |
| Using the variable speed dial | See Fig. G |

The Variable Speed Dial can be used to set the optimum oscillating frequency according to the accessories used and the respective application.

| Oscillation frequency | Application |
|----------------------------|---|
| High oscillation frequency | Sanding, sawing, rasping and polishing stone and metal. |
| Low oscillation frequency | Scraping, polishing varnishes. |

APPLICATION



WARNING: The sawing teeth are very sharp. Do not touch during mounting and application.

The workpiece must be clamped tightly before it is cut.

| | Pic | Description | Application |
|----------------|-----|---|--|
| Sawing | | Extended Life Carbide | Metal, hardened nails and screws, tile, rebar, cement backer board and other heavy duty applications |
| | | Extended Life Bimetal Metal/ Wood End Cut Blade | Wood, plastic, fiberglass, nails, non-ferrous metals, thin sheet metal, hardened fillers |
| | | Precision Wood Cut Blade | Fast Cuts in wood, plastics |
| | | Wood End Cut Blade | Wood, plastic, drywall |
| | | HSS Semicircle Saw Blade | Thin wood, plastic, fiberglass, non-ferrous metals, thin sheet metal, hardened fillers, window glazing |
| Sanding | | Sanding Pad (Perforated) | Wood, plastic, hardened fillers |
| | | Sanding Finger Pad | Wood, plastic, hardened fillers |
| Rasping | | Triangular Carbide Grit Rasp | Wood, hardened adhesives, thin set, masonry |
| | | Carbide Rasp (Finger Shaped) | Wood, hardened adhesives, thin set, masonry |
| Removing grout | | Carbide Grit Semicircle Saw Blade | Grout, porous concrete, masonry |
| | | Diamond-Coated Semicircle Saw Blade | Ceramic and stone tile, backerboard |
| Scraping | | Rigid Scraper Blade | Old paint, hardened adhesives, caulk, carpet |
| | | Flexible Scraper Blade | Elastic sealants, paint, adhesive residues, carpet |

We recommend that you purchase your accessories listed in the above list from the same store that sold you the tool. Refer to the accessory packaging for further details. Store personnel can assist you and offer advice.

NOTE: When plunging and sawing use a slight pendulum motion, to allow sufficient chip removal. The saw blade lasts longer if the wear is distributed evenly. To ensure an even distribution, loosen the saw

blade or other accessory as applicable, rotate it and retighten firmly.
Cut/Sand with a constant movement and light pressure.
Heavy pressure does not increase the cut/removal rate – the accessory merely wears faster.

WORKING HINTS FOR YOUR TOOL


If your power tool becomes too hot, especially when used at low speed, set the speed to maximum and run it with no load for 2-3 minutes to cool the motor. Avoid prolonged usage at very low speeds. Always keep the blade sharp.
Always ensure the work piece is firmly held or clamped to prevent movement. Any movement of the material may affect the quality of the cutting or sanding finish. Start your tool before working and turn it off only after you stop working.
Do not start sanding without having the sandpaper fitted. Do not allow the sandpaper to wear away, it will damage the sanding pad. The guarantee does not cover sanding pad wear and tear.
Use coarse grit paper to sand rough surfaces, medium grit for smooth surfaces and fine grit for finishing surfaces. If necessary, first make a test run on scrap material.
Excessive force will reduce the working efficiency and cause motor overload. Replacing the accessory regularly will maintain optimum working efficiency.

MAINTAIN TOOLS WITH CARE

Remove the plug from the socket before carrying out any adjustment, servicing or maintenance.

Your power tool requires no additional lubrication or maintenance. There are no user serviceable parts in your power tool. Never use water or chemical cleaners to clean your power tool. Wipe clean with a dry cloth. Always store your power tool in a dry place. Keep the motor ventilation slots clean. Keep all working controls free of dust. Occasionally you may see sparks through the ventilation slots. This is normal and will not damage your power tool.
If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid a hazard.

ENVIRONMENTAL PROTECTION

 Waste electrical products must not be disposed of with household waste. Please recycle where facilities exist. Check with your local authorities or retailer for recycling advice.

PLUG REPLACEMENT (ONLY FOR REWIRABLE PLUG OF UK & IRELAND)

If you need to replace the fitted plug then follow the instructions below.

IMPORTANT


The wires in the mains lead are colored in accordance with the following code:

BLUE = NEUTRAL

Brown = Live

As the colors of the wires in the mains lead of this appliance may not correspond with the colored markings identifying the terminals in your plug, proceed as follows. The wire which is colored blue must be connected to the terminal which is marked with N. The wire which is colored brown must be connected to the terminal which is marked with L.
WARNING! Never connect live or neutral wires to the earth terminal of the plug. Only fit an approved 13ABS1363/A plug and the correct rated fuse.

NOTE: If a moulded plug is fitted and has to be removed take great care in disposing of the plug and severed cable, it must be destroyed to prevent engaging into a socket.



DECLARATION OF CONFORMITY

We,
Positec Germany GmbH
Postfach 32 02 16, 50796 Cologne, Germany

Declare that the product
Description **WORX Sonicrafter®**
Type Designation **WX686 (6-designation of machinery, representative of Oscillating Multi-Tool)**
Function **Sanding, sawing, rasping, scraping, polishing**

Complies with the following Directives:

2006/42/EC

2014/30/EU

2011/65/EU&(EU)2015/863

Standards conform to

EN 62841-1

EN 62841-2-4

EN 55014-1

EN 55014-2

EN IEC 61000-3-2

EN 61000-3-3

The person authorized to compile the technical file,

Name: Marcel Filz

Address: Positec Germany GmbH

**Postfach 32 02 16, 50796 Cologne,
Germany**

11



2021/11/22

Allen Ding

Deputy Chief Engineer, Testing & Certification

Positec Technology (China) Co., Ltd

18, Dongwang Road, Suzhou Industrial

Park, Jiangsu 215123, P. R. China

Oscillating Multi-Tool

WX686 WX686.X

DECLARATION OF CONFORMITY

We,
Positec PowerTools (Europe) Ltd,
PO Box 6242, Newbury, RG14 9LT, UK

On behalf of Positec declare that the product
Description **WORX Electric Circular Saw**
Type **WX426 (4-designation of machinery, representative of Saw)**
Function **Cutting various materials with a rotating toothed blade**

Complies with the following regulations:
Supply of Machinery (Safety) Regulations 2008

Electromagnetic Compatibility Regulations 2016

The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations

Standards conform to

BS EN 62841-1
BS EN 62841-2-4
BS EN 55014-1
BS EN 55014-2
BS EN IEC 61000-3-2
BS EN 61000-3-3

The person authorized to compile the technical file,

Name: Jim Kirkwood
Address: Positec Power Tools (Europe) Ltd, PO Box 6242, Newbury, RG14 9LT, UK



2021/11/22

Allen Ding

Deputy Chief Engineer, Testing & Certification
Positec Technology (China) Co., Ltd
18, Dongwang Road, Suzhou Industrial
Park, Jiangsu 215123, P. R. China



you've got the power

After-sales Service and Application

At www.worx.com you can order spare parts or arrange the collection of a product in need of servicing or repair.
Tel. Service: 0345 202 9679
E-Mail: customerservices@worxtools.com

www.worx.com

Copyright © 2020, Positec. All Rights Reserved.
AR01467402